



## SYNOFLEX RESTRAINT FITTINGS

Application	Potable and non-potable systems Suitable for DI, CI, Steel and PE pipes Below and above ground applications
Features	Wide range restraint fitting Joins both flexible and rigid pipes
Size Range:	DN 40 to DN 400
Working Pressure:	PN16 - DN 40 to DN 300 (Water) PN10 - DN 350 to DN 400 (Water)
Deflection:	4 deg Max per end connection
Certification:	WSAA Appraised



COUPLING - UNIVERSAL RESTRAINT			
DN - DN	Range End 1	Range End 2	Code
100 - 100	104 - 132	104 - 132	DGS10
150 - 150	155 - 192	155 - 192	DGS15
200 - 200	198 - 230	198 - 230	DGS20
225 - 225	230 - 260	230 - 260	DGS22
250 - 250	265 - 310	265 - 310	DGS25
300 - 300	313 - 356	313 - 356	DGS30



FLANGE ADAPTOR - UNIVERSAL RESTRAINT			
DN - DN	Range End 1	Flange End 2	Code
100 - 100	104 - 132	100 T/D	DGSF1010
150 - 150	155 - 192	150 T/D	DGSF1515
200 - 200	198 - 230	200 T/D	DGSF2020
225 - 200	230 - 260	200 T/D	DGSF2220
250 - 250	265 - 310	250 T/D	DGSF2525
300 - 300	313 - 356	300 T/D	DGSF3030



END CAP - UNIVERSAL RESTRAINT			
DN	Range	Blank	Tapped 50 BSP
100	104 - 132	DGSB10	DGSB1005
150	155 - 192	DGSB15	DGSB1505
200	198 - 230	DGSB20	DGSB2005
225	230 - 260	DGSB22	DGSB2205
250	265 - 310	DGSB25	DGSB2505
300	313 - 356	DGSB30	DGSB3005

### CIVILPIPES PTY LTD

ABN 30 168 566 667  
2 Potassium St. Narangba Qld 4504  
PO Box 304, North Lakes Qld 4509



Web:  
civilpipes.com.au



Telephone:  
+61 7 3053 3456



E-mail:  
sales@civilpipes.com.au

